







WHEELS MTB



	Predictive Steering XR 1501 SPLINE® ONE 29	Predictive Steering XM 1501 SPLINE® ONE 29	EX 1501 SPLINE® ONE 29
Front wheel	15 / 110 mm TA PS	15 / 110 mm TA PS	15 / 100 mm TA
Rear wheel			12 / 142 mm TA 12 / 142 mm TA XD
Hub	SPLINE® ONE 240s hub with 36-t Ratchet System®, matt black and silver	SPLINE® ONE 240s hub with 36-t Ratchet System®, matt black and silver	SPLINE® ONE 240s hub with 36-t Ratchet System®, matt black and silver
Hubsticker	Waterslide	Waterslide	Waterslide
Brake interface	IS 6-bolt	IS 6-bolt	IS 6-bolt
Rim	Welded, aluminum, sandblasted black	Welded, aluminum, sandblasted black	Welded, aluminum, sandblasted black
Rimsticker	Waterslide	Waterslide	Waterslide
Spokes	Straight pull, DT competition®, black	Straight pull, DT competition®, black	Straight pull, DT competition®, black
Nipples	DT Pro Lock® Squorx, aluminum, silver	DT Pro Lock® Squorx, aluminum, silver	DT Pro Lock® Squorx, aluminum, silver
Lacing	28 x 3-cross	28 x 3-cross	28 x 3-cross
Weight	780 g per wheel ¹⁾	855 g per wheel ¹⁾	1810 g per set ¹⁾
Including	Tubeless ready tape & valve	Tubeless ready tape & valve	Tubeless ready tape & valve, 5 mm front & rear endcaps, 5 mm front & rear RWS MTB steel with aluminum lever

¹⁾ without wheelmounting / lightest combination

WHEELS MTB



X 1700 SPLINE® TWO
27.5 / 29

M 1700 SPLINE® TWO
27.5 / 29

E 1700 SPLINE® TWO
27.5 / 29

Front wheel	15 / 100 mm TA	15 / 100 mm TA	15 / 100 mm TA 20 / 110 mm TA (IS 6-bolt only)
Rear wheel	12 / 142 mm TA 12 / 142 mm TA XD	12 / 142 mm TA 12 / 142 mm TA XD	12 / 142 mm TA 12 / 142 mm TA XD
Hub	SPLINE® hub with Ratchet System®, silver and black	SPLINE® hub with Ratchet System®, silver and black	SPLINE® hub with Ratchet System®, silver and black
Hubsticker	Waterslide	Waterslide	Waterslide
Brake interface	Center Lock® (IS 6-bolt with adaptor)	Center Lock® (IS 6-bolt with adaptor)	Center Lock® (IS 6-bolt with adaptor) ²⁾
Rim	Sleeved, aluminum, black	Sleeved, aluminum, black	Sleeved, aluminum, black
Rimsticker	Waterslide	Waterslide	Waterslide
Spokes	Straight pull, DT competition®, black	Straight pull, DT competition®, black	Straight pull, DT competition®, black
Nipples	DT Pro Lock® Squorx, aluminum, black	DT Pro Lock® Squorx, aluminum, black	DT Pro Lock® Squorx, aluminum, black
Lacing	28 x 3-cross	28 x 3-cross	28 x 3-cross
Weight	27.5 = 1610 g per set ¹⁾ 29 = 1680 g per set ¹⁾	27.5 = 1705 g per set ¹⁾ 29 = 1785 g per set ¹⁾	27.5 = 1840 g per set ¹⁾ 29 = 1910 g per set ¹⁾
Including	IS 6-bolt adaptor, tubeless ready tape & valve, 5 mm front axle & rear endcaps, 5 mm front & rear DT standard QR	IS 6-bolt adaptor, tubeless ready tape & valve, 5 mm front axle & rear endcaps, 5 mm front & rear DT standard QR	IS 6-bolt adaptor ²⁾ , tubeless ready tape & valve, 5 mm rear endcaps, 5 mm rear DT standard QR

¹⁾ without wheelmounting / lightest combination ²⁾ except 20 / 110 mm TA